

CBN Indexable Inserts

-  CBN-P
-  CBN-K
-  CBN-S
-  CBN-H
-  CBN-X



Tool and
Mold Forming



Automotive
Mechanical Engineering



Medical Technology
Microtechnology



Aerospace




PASSION FOR DIAMOND...

ultrahard cutting materials at a glance



... is not just a slogan for us - we live this passion in our daily dealings with our customers and we are your partner when it comes to diamond or CBN tools.



Polycrystalline diamond (PCD)

The well-known Standard Diamond

PCD is a synthetically produced, extremely tough, intergrown mass of diamond particles with a random orientation in a metal matrix. It is produced by sintering selected diamond particles under high pressure and high temperatures.

Graphite serves as a catalyst allowing the PDC crystals to intergrow. PCD has a high thermal conductivity and good heat dissipation away from the cutting edge. In addition, PCD has the highest bending fracture strength of all cutting materials.

PCD is very well suited for machining aluminum with a Si content of up to 12% and/or other abrasive fillers. The thermal hardness is about 750°C. The areas of application are like those of CVD thick-film diamond, but CVD thick film has a higher cost effectiveness with hard-brittle materials or aluminum from a Si content of 12%.

CVD-Thickfilm Diamond (CVD-D)

The Star among Diamond Cutting Materials

For the machining of hard-brittle materials such as Ceramics, glass, glass-Ceramics, tungsten Carbide, MMC and fiber-reinforced composites such as CFRP and GFRP. Due to the lack of a bonding matrix, the diamond content is much higher than with PCD. In the group of ultra-hard cutting materials, binderless CVD-D is one of the hardest man-made diamond cutting materials.

CVD-D is characterized by high hardness as well as high wear resistance. These properties make CVD-D the perfect cutting material for machining abrasive materials. Compared to PCD, which is damaged by the abrasive particles due to its soft metallic binder phase, the CVD-D cutting edge remains stable due to its binderless anchoring in the diamond matrix.

With the correct use of CVD-D, the tool life can be increased by up to 10 times (and even more) compared to PCD!

Binderless Diamond (UltraDiamond)

The hardest Mono Crystal

Single-crystal elements are laser-cut from diamond blanks in a defined orientation using laser segmentation technology. This new technology makes it possible, in addition to polycrystalline cutting materials such as PCD and CVD-D, to also braze a monocrystal (UltraDiamond) under high vacuum on any tool carrier. Compared to PCD, the tool life can be increased by approx. 15 to 25 times and compared to CVD-D by approx. 2 to 5 times.

The areas of application are similar to PCD and CVD-D, but this monocrystalline cutting material offers a further significant increase in tool life in all applications where PCD and CVD-D reach the limits of economic viability. The UltraDiamond cutting material makes economical machining of very hard, highly brittle materials such as Ceramics, glass, glass-Ceramics and hard metals with low cobalt binder and nickel binder (<10%) possible.

Polycrystalline Cubic Boron Nitride (CBN)

Chemically resistant and stable at high temperatures

of up to 1,400°C. Boron nitride powder is the starting point for the production of CBN, which has been available since the end of the 1960s. It is produced under high pressure and at temperatures of over 1,500°C and the many different substrates are specifically adapted to the final application.

CBN is now considered the second hardest material after diamond cutting materials!

The applications of CBN take place in the automotive industry, aerospace, tool and die and mold making as well as in mechanical engineering. The wide range as cutting and abrasive material includes hardened steels, cast irons, chilled cast iron, sintered materials, stellites, nickel- and cobalt-based superalloys. In many applications, cubic boron nitride is preferred to diamond cutting materials because it is absolutely stable in air at temperatures up to 1,400°C. Diamond, on the other hand, begins to decompose at a temperature of approx. 750°C.

Compared to PCD, CBN is also characterized by its chemical resistance to ferrous materials.

Our CBN Grades

and their main applications at a glance

We want to offer you the ideal solution for your application. Therefore, we have developed five CBN-main groups, specially adapted to the requirements of the different materials.

Below you will find an overview of the different groups.



CBN-P
for the machining of *
Sintered Materials

-  continuous cut
-  light interrupted cut
-  heavy interrupted cut



CBN-K
for the highspeed-machining of *
Grey Cast Iron (GCI)
Ductile Cast Iron (DCI)

-  continuous cut
-  light interrupted cut
-  heavy interrupted cut



CBN-S
for the machining of *
Inconel
Ni-, Co-, Fe- and Cr-Alloys

-  continuous cut
-  light interrupted cut
-  heavy interrupted cut



CBN-H
for the machining of *
Steel, hardened up to 72 HRC
Sinter Steel, hardened

-  continuous cut
-  light interrupted cut
-  heavy interrupted cut



CBN-X
for the machining of *
Powder metallurgical Steel, hardened
Special Alloys such as ASP, CPM, Hardox
Tool Steel, hardened up to 72 HRC

-  continuous cut
-  light interrupted cut
-  heavy interrupted cut

* all other applications can be found in the complete cutting material assignment on page 7

Our Cutting Material Assignment

about the materials

You cannot find your material in the table?

We are glad to help you by phone or by mail!

Phone: 888.554.7264

Mail: sales@ranitool.com

Green ✓

Orange ✓

First choice


Possible alternative

ISO	Material	CBN-P	CBN-K	CBN-S	CBN-H	CBN-X
H	Powder metallurgical Steel, hardened	Orange ✓				Green ✓
	Special Alloys (ASP,CPM,Hardox)			Orange ✓		Green ✓
	Steel, hardened up to 72 HRC	Orange ✓			Green ✓	
	Tool Steel, hardened up to 72 HRC	Orange ✓				Green ✓
P	Sintered Steel	Green ✓				Orange ✓
	Sintered Steel, hardened			Orange ✓	Green ✓	
K	Grey Cast Iron (GCI)		Green ✓	Orange ✓		
	Ductile Cast Iron (DCI)		Green ✓	Orange ✓		
	Shell Chilled Cast Iron	Orange ✓			Green ✓	
S	Ni-, Co-, Fe- and Cr-Alloys			Green ✓		Orange ✓
	Titanium Alloys			Green ✓		Orange ✓
M	Stainless Steel, hardened				Orange ✓	Green ✓
N	Carbide, > 20% Co * <small>*for the machining of carbide we recommend the use of CVD-D inserts</small>					Green ✓

Wiper Indexable Inserts

Functionality

Wiper Indexable Inserts:



Advantages when using Wiper Geometries

By using the same feed rate a 2-4 times better surface quality can be obtained or with a 2-4 times higher feed rate the same surface quality can be reached.

To get the wiper geometry into cutting condition please use the following lead angles at the machine:

C and W Type: 95°

D Typ: 93°

CCGW ...
(Z2)



CNGA ...
(Z2)



DCGW ...
(Z2)




ISO Code

CBN Indexable Inserts

Shape

T N G A 16 04 08



Clearance

T N G A 16 04 08



Tolerance [mm]


T N G A 16 04 08

	m	s	d		m	s	d
A	±0,005	±0,025	±0,025	J	±0,005	±0,025	±0,05 → ±0,15
F	±0,005	±0,025	±0,013	K	±0,013	±0,025	±0,05 → ±0,15
C	±0,013	±0,025	±0,025	L	±0,025	±0,025	±0,05 → ±0,15
H	±0,013	±0,025	±0,013	M	±0,08 → ±0,008	±0,130	±0,05 → ±0,15
E	±0,025	±0,025	±0,025	N	±0,08 → ±0,20	±0,25	±0,05 → ±0,15
G	±0,025	±0,130	±0,025	U	±0,13 → ±0,38	±0,130	±0,08 → ±0,15

*[M, N, U] The exact tolerance depends on the size of the insert.


Insert Type

T N G A 16 04 08



Insert size [mm]

T N G A 16 04 08



Insert size [mm]

T N G A 16 04 08

01	S = .062	T1	S = .078	02	S = .094	03	S = .125	T3	S = .156	04	S = .187	05	S = .219	06	S = .250
----	----------	----	----------	----	----------	----	----------	----	----------	----	----------	----	----------	----	----------

By numbers below 10 a 0 is added in at the front. Decimals remain unconsidered (for example: 4,76 = 04)


Corner configuration [mm]

T N G A 16 04 08



CCGW

edge tipped



	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH ^{New}
					Item No.				
Standard	CCGW-21.50-2	.250	.094	.004			TI5510-0139		
	CCGW-21.50.5-2	.250	.094	.008	TI5510-0140	TI5510-0141	TI5510-0142	TI5510-0143	TI5510-3102
	CCGW-21.51-2	.250	.094	.016	TI5510-0145	TI5510-0146	TI5510-0147	TI5510-0148	TI5510-3104
	CCGW-21.52-2	.250	.094	.031	TI5510-0150	TI5510-0151	TI5510-0152	TI5510-0153	TI5510-3106
	CCGW-32.50-2	.375	.156	.004			TI5510-1205		
	CCGW-32.50.5-2	.375	.156	.008	TI5510-0160	TI5510-0161	TI5510-0162	TI5510-0163	TI5510-3112
	CCGW-32.51-2	.375	.156	.016	TI5510-0165	TI5510-0166	TI5510-0167	TI5510-0168	TI5510-3114
	CCGW-32.52-2	.375	.156	.031	TI5510-0170	TI5510-0171	TI5510-0172	TI5510-0173	TI5510-3116
	CCGW-430.5-2	.500	.156	.008	TI5510-0180	TI5510-0181	TI5510-0182	TI5510-0183	TI5510-3122
	CCGW 431-2	.500	.187	.016	TI5510-0185	TI5510-0186	TI5510-0187	TI5510-0188	TI5510-3124
Sharp	CCGW 432-2	.500	.187	.031	TI5510-0190	TI5510-0191	TI5510-0192	TI5510-0193	TI5510-3126
	CCGW 433-2	.500	.187	.047	TI5510-0195	TI5510-0196	TI5510-0197	TI5510-0198	TI5510-3128
	CCGW-21.50.5F-2	.250	.094	.008	TI5510-2302	TI5510-2402	TI5510-2602	TI5510-2702	TI5510-2802
	CCGW-21.51F-2	.250	.094	.016	TI5510-2304	TI5510-2404	TI5510-2604	TI5510-2704	TI5510-2804
Wiper	CCGW-32.50.5F-2	.375	.156	.008	TI5510-2312	TI5510-2412	TI5510-2612	TI5510-2712	TI5510-2812
	CCGW-32.51F-2	.375	.156	.016	TI5510-2314	TI5510-2414	TI5510-2614	TI5510-2714	TI5510-2814
	CCGW-32.50.5W-2	.375	.156	.008	TI5510-0205	TI5510-0206	TI5510-0207	TI5510-0208	
	CCGW-32.51W-2	.375	.156	.016	TI5510-0210	TI5510-0211	TI5510-0212	TI5510-0213	TI5510-3144
	CCGW-32.52W-2	.375	.156	.031	TI5510-0215	TI5510-0216	TI5510-0217	TI5510-0218	TI5510-3146
	CCGW-431W-2	.500	.187	.016	TI5510-0225	TI5510-0226	TI5510-0227	TI5510-0228	TI5510-3154
CCGW-432W-2	.500	.187	.031	TI5510-0230	TI5510-0231	TI5510-0232	TI5510-0233	TI5510-3156	
CCGW-433W-2	.500	.187	.047	TI5510-0235	TI5510-0236	TI5510-0237	TI5510-0238	TI5510-3158	

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL ^{New}	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH ^{New}	Version
TI5010-0139	TI5010-3102	TI5010-0141	TI5010-0142	TI5010-0143	TI5910-0139	TI5910-0142	2-edge tipped
TI5010-0140	TI5010-3104	TI5010-0146	TI5010-0147	TI5010-0148	TI5910-0144	TI5910-0147	2-edge tipped
TI5010-0145	TI5010-3106	TI5010-0151	TI5010-0152	TI5010-0153	TI5910-0146	TI5910-0149	2-edge tipped
TI5010-0150	TI5010-3112	TI5010-0161	TI5010-0162	TI5010-0163	TI5910-0148	TI5910-0151	2-edge tipped
TI5010-1205	TI5010-3114	TI5010-0166	TI5010-0167	TI5010-0168	TI5910-0150	TI5910-0153	2-edge tipped
TI5010-0160	TI5010-3116	TI5010-0171	TI5010-0172	TI5010-0173	TI5910-0152	TI5910-0155	2-edge tipped
TI5010-0165	TI5010-3122	TI5010-0181	TI5010-0182	TI5010-0183	TI5910-0154	TI5910-0157	2-edge tipped
TI5010-0170	TI5010-3124	TI5010-0186	TI5010-0187	TI5010-0188	TI5910-0156	TI5910-0159	2-edge tipped
TI5010-0180	TI5010-3126	TI5010-0191	TI5010-0192	TI5010-0193	TI5910-0158	TI5910-0161	2-edge tipped
TI5010-0185	TI5010-3128	TI5010-0196	TI5010-0197	TI5010-0198	TI5910-0160	TI5910-0163	2-edge tipped
TI5010-0190	TI5010-2502	TI5010-2602	TI5010-2702		TI5910-0162	TI5910-0165	2-edge tipped
TI5010-0195	TI5010-2504	TI5010-2604	TI5010-2704		TI5910-0164	TI5910-0167	2-edge tipped
TI5010-2402	TI5010-2512	TI5010-2612	TI5010-2712		TI5910-0166	TI5910-0169	2-edge tipped
TI5010-2404	TI5010-2514	TI5010-2614	TI5010-2714		TI5910-0168	TI5910-0171	2-edge tipped
TI5010-2412					TI5910-0170	TI5910-0173	2-edge tipped
TI5010-2414					TI5910-0172	TI5910-0175	2-edge tipped
TI5010-0210					TI5910-0174	TI5910-0177	2-edge tipped
TI5010-0215					TI5910-0176	TI5910-0179	2-edge tipped
TI5010-0225					TI5910-0178	TI5910-0181	2-edge tipped
TI5010-0230					TI5910-0180	TI5910-0183	2-edge tipped
TI5010-0235					TI5910-0182	TI5910-0185	2-edge tipped

Special tools on request for you!
Please send inquiries to sales@ranitool.com


All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.

Subject to technical changes.


CDGW

FullFace | edge tipped



New	ISO Code	IC	S	R	P25BH	P45BH	K65BH ^{New}	K85BH	S85BH
					Item No.	Item No.	Item No.	Item No.	Item No.
	CDGW 03X101-Right	.126	.025	.004			TI5530-0500		
	CDGW 03X102-Right	.126	.025	.008			TI5530-0502		
	CDGW 03X101-Left	.126	.025	.004			TI5530-0501		
	CDGW 03X102-Left	.126	.025	.008			TI5530-0503		

! You will find the matching boring bar holder in our boring bar catalog [03] on page 19.



New	ISO Code	IC	S	R	P25BH	P45BH	K85BH ^{New}	K85BH	S85BH
					Item No.	Item No.	Item No.	Item No.	Item No.
	CDGW-040101-2	.156	.039	.004			TI5510-2510		
	CDGW-040102-2	.156	.039	.008			TI5510-2512		
	CDGW-040104-2	.156	.039	.016			TI5510-2514		

! You will find the matching boring bar holder in our boring bar catalog [03] on page 22.

i Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL	H45BL	H65BL ^{New}	H85BL	X90BH ^{New}	X95BH	Version
			TI5030-0500		TI5930-0500		FullFace (Z1)
			TI5030-0502		TI5930-0502		FullFace (Z1)
			TI5030-0501		TI5930-0501		FullFace (Z1)
			TI5030-0503		TI5930-0503		FullFace (Z1)

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH	Version
			TI5010-1511		TI5910-2510		2-edge tipped
			TI5010-1512		TI5910-2512		2-edge tipped
			TI5010-1513		TI5910-2514		2-edge tipped

Special tools on request for you! Please send inquiries to sales@ranitool.com

All our products are also available in the online shop. Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.

Subject to technical changes.



Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...


You will find further application ranges in the detailed overview on page 7.

CNGA

edge tipped



	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH ^{New}
					Item No.				
Standard	CNGA-430.5-2	.500	.187	.008	TI5510-0245	TI5510-0246	TI5510-0247	TI5510-0248	TI5510-3202
	CNGA-431-2	.500	.187	.016	TI5510-0250	TI5510-0251	TI5510-0252	TI5510-0253	TI5510-3204
	CNGA-432-2	.500	.187	.031	TI5510-0255	TI5510-0256	TI5510-0257	TI5510-0258	TI5510-3206
	CNGA-433-2	.500	.187	.047	TI5510-0260	TI5510-0261	TI5510-0262	TI5510-0263	TI5510-3208
Wiper	CNGA-430.5W-2	.500	.187	.008	TI5510-0270	TI5510-0271	TI5510-0272	TI5510-0273	TI5510-3222
	CNGA-431W-2	.500	.187	.016	TI5510-0275	TI5510-0276	TI5510-0277	TI5510-0278	TI5510-3224
	CNGA-432W-2	.500	.187	.031	TI5510-0280	TI5510-0281	TI5510-0282	TI5510-0283	TI5510-3226
	CNGA-433W-2	.500	.187	.047	TI5510-0285	TI5510-0286	TI5510-0287	TI5510-0288	TI5510-3228



	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.	Item No.	Item No.	Item No.	Item No.
Standard	CNGA-430.5-4	.500	.187	.008	TI5510-0295	TI5510-0296	TI5510-0297	TI5510-0298	
	CNGA-431-4	.500	.187	.016	TI5510-0300	TI5510-0301	TI5510-0302	TI5510-0303	
	CNGA-432-4	.500	.187	.031	TI5510-0305	TI5510-0306	TI5510-0307	TI5510-0308	
	CNGA-433-4	.500	.187	.047	TI5510-0310	TI5510-0311	TI5510-0312	TI5510-0313	
Wiper	CNGA-430.5W-4	.500	.187	.008	TI5510-0320	TI5510-0321	TI5510-0322	TI5910-0323	
	CNGA-431W-4	.500	.187	.016	TI5510-0325	TI5510-0326	TI5510-0327	TI5510-0328	
	CNGA-432W-4	.500	.187	.031	TI5510-0330	TI5510-0331	TI5510-0332	TI5510-0333	
	CNGA-433W-4	.500	.187	.047	TI5510-0335	TI5510-0336	TI5510-0337	TI5510-0338	

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

	H25BL	H35E ^{New}	H45BL	H65BL	H85BL	X90E ^{New}	X95E ^{New}	Version
	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
TI5010-0245	TI5010-3202	TI5010-0246	TI5010-0247	TI5010-0248	TI5910-0247	TI5910-0248	2-edge tipped	
TI5010-0250	TI5010-3204	TI5010-0251	TI5010-0252	TI5010-0253	TI5910-0252	TI5910-0253	2-edge tipped	
TI5010-0255	TI5010-3206	TI5010-0256	TI5010-0257	TI5010-0258	TI5910-0257	TI5910-0258	2-edge tipped	
TI5010-0260	TI5010-3208	TI5010-0261	TI5010-0262	TI5010-0263	TI5910-0262	TI5910-0263	2-edge tipped	
TI5010-0270	TI5010-3222	TI5010-0271	TI5010-0272	TI5010-0273	TI5910-0272	TI5910-0273	2-edge tipped	
TI5010-0275	TI5010-3224	TI5010-0276	TI5010-0277	TI5010-0278	TI5910-0277	TI5910-0278	2-edge tipped	
TI5010-0280	TI5010-3226	TI5010-0281	TI5010-0282	TI5010-0283	TI5910-0282	TI5910-0283	2-edge tipped	
TI5010-0285	TI5010-3228	TI5010-0286	TI5010-0287	TI5010-0288	TI5910-0287	TI5910-0288	2-edge tipped	

	H25BL	H35BL	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH ^{New}	Version
	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
TI5010-0295			TI5010-0296	TI5010-0297	TI5010-0298	TI5910-0297	TI5910-0298	4-edge tipped
TI5010-0300			TI5010-0301	TI5010-0302	TI5010-0303	TI5910-0302	TI5910-0303	4-edge tipped
TI5010-0305			TI5010-0306	TI5010-0307	TI5010-0308	TI5910-0307	TI5910-0308	4-edge tipped
TI5010-0310			TI5010-0311	TI5010-0312	TI5010-0313	TI5910-0312	TI5910-0313	4-edge tipped
TI5010-0320			TI5010-0321	TI5010-0322	TI5010-0323	TI5910-0322	TI5910-0323	4-edge tipped
TI5010-0325			TI5010-0326	TI5010-0327	TI5010-0328	TI5910-0327	TI5910-0328	4-edge tipped
TI5010-0330			TI5010-0331	TI5010-0332	TI5010-0333	TI5910-0332	TI5910-0333	4-edge tipped
TI5010-0335			TI5010-0336	TI5010-0337	TI5010-0338	TI5910-0337	TI5910-0338	4-edge tipped

Special tools on request for you!
Please send inquiries to sales@ranitool.com



All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.


Subject to technical changes.

DNGA

edge tipped



	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH ^{New}
					Item No.				
Standard	DNGA-430.5-2	.500	.187	.004			TI5510-0472		
	DNGA-431-2	.500	.187	.008	TI5510-0475	TI5510-0476	TI5510-0477	TI5510-0478	TI5510-3402
	DNGA-431-2	.500	.187	.016	TI5510-0480	TI5510-0481	TI5510-0482	TI5510-0483	TI5510-3404
	DNGA-432-2	.500	.187	.031	TI5510-0485	TI5510-0486	TI5510-0487	TI5510-0488	TI5510-3406
	DNGA-433-2	.500	.187	.047	TI5510-0490	TI5510-0491	TI5510-0492	TI5510-0493	TI5510-3408
Wiper	DNGA-431W-2	.500	.187	.016	TI5510-0525	TI5510-0526	TI5510-0527	TI5510-0528	TI5510-3444
	DNGA-432W-2	.500	.187	.031	TI5510-0530	TI5510-0531	TI5510-0532	TI5510-0533	TI5510-3446



	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.	Item No.	Item No.	Item No.	Item No.
Standard	DNGA-430.5-4	.500	.187	.008	TI5510-0570	TI5510-0571	TI5510-0572	TI5510-0573	
	DNGA-431-4	.500	.187	.016	TI5510-0575	TI5510-0576	TI5510-0577	TI5510-0578	
	DNGA-432-4	.500	.187	.031	TI5510-0580	TI5510-0581	TI5510-0582	TI5510-0583	
	DNGA-433-4	.500	.187	.047	TI5510-0585	TI5510-0586	TI5510-0587	TI5510-0588	
Wiper	DNGA-431W-4	.500	.187	.016	TI5510-0620	TI5510-0621	TI5510-0622	TI5510-0623	
	DNGA-432W-4	.500	.187	.031	TI5510-0625	TI5510-0626	TI5510-0627	TI5510-0628	

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL ^{New}	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH ^{New}	Version
TI5010-0470	TI5010-3402	TI5010-0476	TI5010-0477	TI5010-0478	TI5910-0472	TI5910-0478	2-edge tipped
TI5010-0475	TI5010-3404	TI5010-0481	TI5010-0482	TI5010-0483	TI5910-0477	TI5910-0483	2-edge tipped
TI5010-0480	TI5010-3406	TI5010-0486	TI5010-0487	TI5010-0488	TI5910-0482	TI5910-0488	2-edge tipped
TI5010-0485	TI5010-3408	TI5010-0491	TI5010-0492	TI5010-0493	TI5910-0487	TI5910-0488	2-edge tipped
TI5010-0490					TI5910-0492	TI5910-0493	2-edge tipped
TI5010-0525	TI5010-3444	TI5010-0526	TI5010-0527	TI5010-0528	TI5910-0527	TI5910-0528	2-edge tipped
TI5010-0530	TI5010-3446	TI5010-0531	TI5010-0532	TI5010-0533	TI5910-0532	TI5910-0533	2-edge tipped

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH ^{New}	Version
TI5010-0570		TI5010-0571	TI5010-0572	TI5010-0573	TI5910-0572	TI5910-0573	4-edge tipped
TI5010-0575		TI5010-0576	TI5010-0577	TI5010-0578	TI5910-0577	TI5910-0578	4-edge tipped
TI5010-0580		TI5010-0581	TI5010-0582	TI5010-0583	TI5910-0582	TI5910-0583	4-edge tipped
TI5010-0585		TI5010-0586	TI5010-0587	TI5010-0588	TI5910-0587	TI5910-0588	4-edge tipped
TI5010-0620		TI5010-0621	TI5010-0622	TI5010-0623	TI5910-0622	TI5910-0623	4-edge tipped
TI5010-0625		TI5010-0626	TI5010-0627	TI5010-0628	TI5910-0627	TI5910-0628	4-edge tipped

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com



All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.


Subject to technical changes.

DNGA

edge tipped



	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH New
					Item No.				
Standard	DNGA-440-2	.500	.250	.004			TI5510-0497		
	DNGA-440.5-2	.500	.250	.008	TI5510-0500	TI5510-0501	TI5510-0502	TI5510-0503	TI5510-3422
	DNGA-441-2	.500	.250	.016	TI5510-0505	TI5510-0506	TI5510-0507	TI5510-0508	TI5510-3424
	DNGA-442-2	.500	.250	.031	TI5510-0510	TI5510-0511	TI5510-0512	TI5510-0513	TI5510-3426
	DNGA-443-2	.500	.250	.047	TI5510-0515	TI5510-0516	TI5510-0517	TI5510-0518	TI5510-3428
Wiper	DNGA-441W-2	.500	.250	.016	TI5510-0535	TI5510-0536	TI5510-0537	TI5510-0538	TI5510-3464
	DNGA-442W-2	.500	.250	.031	TI5510-0540	TI5510-0541	TI5510-0542	TI5510-0543	TI5510-3466



	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.	Item No.	Item No.	Item No.	Item No.
Standard	DNGA-440.5-4	.500	.250	.008	TI5510-0595	TI5510-0596	TI5510-0597	TI5510-0598	
	DNGA-441-4	.500	.250	.016	TI5510-0600	TI5510-0601	TI5510-0602	TI5510-0603	
	DNGA-442-4	.500	.250	.031	TI5510-0605	TI5510-0606	TI5510-0607	TI5510-0608	
	DNGA-443-4	.500	.250	.047	TI5510-0610	TI5510-0611	TI5510-0612	TI5510-0613	
Wiper	DNGA-441W-4	.500	.250	.016	TI5510-0630	TI5510-0631	TI5510-0632	TI5510-0633	
	DNGA-442W-4	.500	.250	.031	TI5510-0635	TI5510-0636	TI5510-0637	TI5510-0638	

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL New	H45BL	H65BL	H85BL	X90BH New	X95BH New	Version
TI5010-0495					TI5910-0497		2-edge tipped
TI5010-0500	TI5010-3422	TI5010-0501	TI5010-0502	TI5010-0503	TI5910-0502	TI5910-0503	2-edge tipped
TI5010-0505	TI5010-3424	TI5010-0506	TI5010-0507	TI5010-0508	TI5910-0507	TI5910-0508	2-edge tipped
TI5010-0510	TI5010-3426	TI5010-0511	TI5010-0512	TI5010-0513	TI5910-0512	TI5910-0513	2-edge tipped
TI5010-0515	TI5010-3428	TI5010-0516	TI5010-0517	TI5010-0518	TI5910-0517	TI5910-0518	2-edge tipped
TI5010-0535	TI5010-3464	TI5010-0536	TI5010-0537	TI5010-0538	TI5910-0537	TI5910-0538	2-edge tipped
TI5010-0540	TI5010-3466	TI5010-0541	TI5010-0542	TI5010-0543	TI5910-0542	TI5910-0543	2-edge tipped

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH New	X95BH New	Version
TI5010-0595		TI5010-0596	TI5010-0597	TI5010-0598	TI5910-0597	TI5910-0598	4-edge tipped
TI5010-0600		TI5010-0601	TI5010-0602	TI5010-0603	TI5910-0602	TI5910-0603	4-edge tipped
TI5010-0605		TI5010-0606	TI5010-0607	TI5010-0608	TI5910-0607	TI5910-0608	4-edge tipped
TI5010-0610		TI5010-0611	TI5010-0612	TI5010-0613	TI5910-0612	TI5910-0613	4-edge tipped
TI5010-0630		TI5010-0631	TI5010-0632	TI5010-0633	TI5910-0632	TI5910-0633	4-edge tipped
TI5010-0635		TI5010-0636	TI5010-0637	TI5010-0638	TI5910-0637	TI5910-0638	4-edge tipped

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com


All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.

Subject to technical changes.

ODGW

FullFace



FullFace

	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.	Item No.	Item No.	Item No.	Item No.
Standard	ODGW 05T302	.500	.156	.008			MI5530-0100		
	ODGW 05T304	.500	.156	.016			MI5530-0102		
	ODGW 05T308	.500	.156	.031			MI5530-0104		

i Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
			MI5030-0100		MI5930-0100		FullFace (Z8)
			MI5030-0102		MI5930-0102		FullFace (Z8)
			MI5030-0104		MI5930-0104		FullFace (Z8)

i Turning and milling inserts (8-edged)

You can find suitable milling heads in our milling systems with indexable inserts catalog (05).

You can find suitable external clamp holders in our online shop.

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com

All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.

Subject to technical changes.


RBGN | RCGW

FullFace



Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut




FullFace

Standard

ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
				Item No.	Item No.	Item No.	Item No.	Item No.
RBGN 0602M0	6,00	.094	-			T15530-0090		
RBGN 0803M0	8,00	.125	-			T15530-0092		
RBGN 1003M0	10,00	.125	-			T15530-0094		
RBGN 1203M0	12,00	.125	-			T15530-0096		

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
			T15030-0090		T15930-0090		FullFace
			T15030-0092		T15930-0092		FullFace
			T15030-0094		T15930-0094		FullFace
			T15030-0096		T15930-0096		FullFace



FullFace

Standard

ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
				Item No.	Item No.	Item No.	Item No.	Item No.
RCGW 0602M0	6,00	.094	-			T15530-0102		
RCGW 0803M0	8,00	.125	-			T15530-0107		
RCGW 1003M0	10,00	.125	-			T15530-0117		
RCGW 10T3M0	10,00	.156	-			T15530-0122		
RCGW 1204M0	12,00	.187	-			T15530-0127		

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
			T15030-0100		T15930-0102		FullFace
			T15030-0105		T15930-0107		FullFace
			T15030-0115		T15930-0117		FullFace
			T15030-0120		T15930-0122		FullFace
			T15030-0125		T15930-0127		FullFace

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Werkzeugstah hardened I, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com

All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.

Subject to technical changes.


RNGN

Solid



Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut



Solid

	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.				
Standard	RNGN 060300	.250	.125	-					
	RNGN 060400	.250	.187	-					
	RNGN 090300	.375	.125	-					
	RNGN 090400	.375	.187	-					
	RNGN 120300	.500	.125	-					
	RNGN 120400	.500	.187	-					

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Version
							Solid
			TI5040-0090		TI5940-0090		Solid
			TI5040-0091		TI5940-0091		Solid
			TI5040-0100		TI5940-0100		Solid
			TI5040-0105		TI5940-0105		Solid
			TI5040-0115		TI5940-0115		Solid
			TI5040-0120		TI5940-0120		Solid

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com


All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.

Subject to technical changes.

SCGW

edge tipped



	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.	Item No.	Item No.	Item No.	Item No.
Standard	SCGW-32.50.5-4	.375	.156	.008	TI5510-0645	TI5510-0646	TI5510-0647	TI5510-0648	
	SCGW-32.51-4	.375	.156	.016	TI5510-0650	TI5510-0651	TI5510-0652	TI5510-0653	
	SCGW-32.52-2	.375	.156	.031	TI5510-0655	TI5510-0656	TI5510-0657	TI5510-0658	
	SCGW-430.5	.500	.187	.008	TI5510-0665	TI5510-0666	TI5010-0667	TI5510-0668	
	SCGW-431-4	.500	.187	.016	TI5510-0670	TI5510-0671	TI5510-0672	TI5510-0673	
	SCGW-432-4	.500	.187	.031	TI5510-0675	TI5510-0676	TI5510-0677	TI5510-0678	
	SCGW-433-4	.500	.187	.047	TI5510-0680	TI5510-0681	TI5510-0682	TI5510-0683	

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH ^{New}	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
TI5010-0645		TI5010-0646	TI5010-0647	TI5010-0648	TI5910-0647	TI5910-0648	4-edge tipped
TI5010-0650		TI5010-0651	TI5010-0652	TI5010-0653	TI5910-0652	TI5910-0653	4-edge tipped
TI5010-0655		TI5010-0656	TI5010-0657	TI5010-0658	TI5910-0657	TI5910-0658	4-edge tipped
TI5010-0665		TI5010-0666	TI5010-0667	TI5010-0668	TI5910-0667	TI5910-0668	4-edge tipped
TI5010-0670		TI5010-0671	TI5010-0672	TI5010-0673	TI5910-0672	TI5910-0673	4-edge tipped
TI5010-0675		TI5010-0676	TI5010-0677	TI5010-0678	TI5910-0677	TI5910-0678	4-edge tipped
TI5010-0680		TI5010-0681	TI5010-0682	TI5010-0683	TI5910-0682	TI5910-0683	4-edge tipped

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com



All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.

Subject to technical changes.


SNGA

edge tipped



CL 3,00 mm
4-edge tipped

	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.	Item No.	Item No.	Item No.	Item No.
Standard	SNGA-431-4	.500	.187	.016	TI5510-0690	TI5510-0691	TI5510-0692	TI5510-0693	
	SNGA-432-4	.500	.187	.031	TI5510-0695	TI5510-0696	TI5510-0697	TI5510-0698	
	SNGA-433-4	.500	.187	.047	TI5510-0700	TI5510-0701	TI5510-0702	TI5510-0703	



CL 3,00 mm
8-edge tipped

	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.	Item No.	Item No.	Item No.	Item No.
Standard	SNGA-431-8	.500	.187	.016	TI5510-0710	TI5510-0711	TI5510-0712	TI5510-0713	
	SNGA-432-8	.500	.187	.031	TI5510-0715	TI5510-0716	TI5510-0717	TI5510-0718	
	SNGA-433-8	.500	.187	.047	TI5510-0720	TI5510-0721	TI5510-0722	TI5510-0723	

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH ^{New}	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
TI5010-0690		TI5010-0691	TI5010-0692	TI5010-0693	TI5910-0692	TI5910-0693	4-edge tipped
TI5010-0695		TI5010-0696	TI5010-0697	TI5010-0698	TI5910-0697	TI5910-0698	4-edge tipped
TI5010-0700		TI5010-0701	TI5010-0702	TI5010-0703	TI5910-0702	TI5910-0703	4-edge tipped

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH ^{New}	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
TI5010-0710		TI5010-0711	TI5010-0712	TI5010-0713	TI5910-0712	TI5910-0713	8-edge tipped
TI5010-0715		TI5010-0716	TI5010-0717	TI5010-0718	TI5910-0717	TI5910-0718	8-edge tipped
TI5010-0720		TI5010-0721	TI5010-0722	TI5010-0723	TI5910-0722	TI5910-0723	8-edge tipped

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com


All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete **holder program** in our tool holder catalog or in our online shop.

Subject to technical changes.

SNGN

Solid



Solid

Standard

ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
				Item No.	Item No.	Item No.	Item No.	Item No.
SNGN-321-8	.375	.125	.016			TI5540-0130		
SNGN-322-8	.375	.125	.031			TI5540-0135		
SNGN-323-8	.375	.125	.047			TI5540-0140		
SNGN-431-8	.500	.187	.016			TI5540-0145		
SNGN-432-8	.500	.187	.031			TI5540-0150		
SNGN-433-8	.500	.187	.047			TI5540-0155		
SNGN-434-8	.500	.187	.062			TI5540-0160		

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH ^{New}	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
			TI5040-0130		TI5940-0130		Solid
			TI5040-0135		TI5940-0135		Solid
			TI5040-0140		TI5940-0140		Solid
			TI5040-0145		TI5940-0145		Solid
			TI5040-0150		TI5940-0150		Solid
			TI5040-0155		TI5940-0155		Solid
			TI5040-0160		TI5940-0160		Solid

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com


All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete **holder program** in our tool holder catalog or in our online shop.

Subject to technical changes.

TCGW

edge tipped



Standard

ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH New
				Item No.				
TCGW-1.81.50-3	.219	.094	.004					
TCGW-1.81.50.5-3	.219	.094	.008	TI5510-0730	TI5510-0731	TI5510-0732	TI5510-0733	TI5510-3502
TCGW-1.81.51-3	.219	.094	.016	TI5510-0735	TI5510-0736	TI5510-0737	TI5510-0738	TI5510-3504
TCGW-1.81.52-3	.219	.094	.031	TI5510-0740	TI5510-0741	TI5510-0742	TI5510-0743	TI5510-3506
TCGW-21.50-3	.250	.094	.004					
TCGW-21.50.5-3	.250	.094	.008	TI5510-0750	TI5510-0751	TI5510-0752	TI5510-0753	TI5510-3522
TCGW 21.51-3	.250	.094	.016	TI5510-0755	TI5510-0756	TI5510-0757	TI5510-0758	TI5510-3524
TCGW-21.52-3	.250	.094	.031	TI5510-0760	TI5510-0761	TI5510-0762	TI5510-0763	TI5510-3526
TCGW-32.50.5-3	.375	.156	.008	TI5510-0770	TI5510-0771	TI5510-0772	TI5510-0773	TI5510-3542
TCGW-32.51-3	.375	.156	.016	TI5510-0775	TI5510-0776	TI5510-0777	TI5510-0778	TI5510-3544
TCGW-32.52-3	.375	.156	.031	TI5510-0780	TI5510-0781	TI5510-0782	TI5510-0783	TI5510-3546

i Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL New	H45BL	H65BL	H85BL	X90BH New	X95BH New	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
TI5010-0725							3-edge tipped
TI5010-0730	TI5010-3502	TI5010-0731	TI5010-0732	TI5010-0733	TI5910-0732	TI5910-0733	3-edge tipped
TI5010-0735	TI5010-3504	TI5010-0736	TI5010-0737	TI5010-0738	TI5910-0737	TI5910-0738	3-edge tipped
TI5010-0740	TI5010-3506	TI5010-0741	TI5010-0742	TI5010-0743	TI5910-0742	TI5910-0743	3-edge tipped
TI5010-0745							3-edge tipped
TI5010-0750	TI5010-3522	TI5010-0751	TI5010-0752	TI5010-0753	TI5910-0752	TI5910-0753	3-edge tipped
TI5010-0755	TI5010-3524	TI5010-0556	TI5010-0757	TI5010-0758	TI5910-0757	TI5910-0758	3-edge tipped
TI5010-0760	TI5010-3526	TI5010-0761	TI5010-0762	TI5010-0763	TI5910-0762	TI5910-0763	3-edge tipped
TI5010-0770	TI5010-3542	TI5010-0771	TI5010-0772	TI5010-0773	TI5910-0772	TI5910-0773	3-edge tipped
TI5010-0775	TI5010-3544	TI5010-0776	TI5010-0777	TI5010-0778	TI5910-0777	TI5910-0778	3-edge tipped
TI5010-0780	TI5010-3546	TI5010-0781	TI5010-0782	TI5010-0783	TI5910-0782	TI5910-0783	3-edge tipped

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com


All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete **holder program** in our tool holder catalog or in our online shop.

Subject to technical changes.


TNGA

edge tipped



CL 3,00 mm
3-edge tipped

	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.				
Standard	TNGA-330.5-3	.375	.187	.008	TI5510-0790	TI5510-0791	TI5510-0792	TI5510-0793	TI5510-3602
	TNGA-331-3	.375	.187	.016	TI5510-0795	TI5510-0796	TI5510-0797	TI5510-0798	TI5510-3604
	TNGA-332-3	.375	.187	.031	TI5510-0800	TI5510-0801	TI5510-0802	TI5510-0803	TI5510-3606
	TNGA-333-3	.375	.187	.047	TI5510-0805	TI5510-0806	TI5510-0807	TI5510-0808	TI5510-3608



CL 3,00 mm
6-edge tipped

	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.	Item No.	Item No.	Item No.	Item No.
Standard	TNGA-330.5-6	.375	.187	.008	TI5510-0815	TI5510-0816	TI5510-0817	TI5510-0818	
	TNGA-331-6	.375	.187	.016	TI5510-0820	TI5510-0821	TI5510-0822	TI5510-0823	
	TNGA-332-6	.375	.187	.031	TI5510-0825	TI5510-0826	TI5510-0827	TI5510-0828	
	TNGA-333-6	.375	.187	.047	TI5510-0830	TI5510-0831	TI5510-0832	TI5510-0833	

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL ^{low}	H45BL	H65BL	H85BL	X90BH	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
TI5010-0790	TI5010-3602	TI5010-0791	TI5010-0792	TI5010-0793	TI5910-0792	TI5910-0793	3-edge tipped
TI5010-0795	TI5010-3604	TI5010-0796	TI5010-0797	TI5010-0798	TI5910-0797	TI5910-0798	3-edge tipped
TI5010-0800	TI5010-3606	TI5010-0801	TI5010-0802	TI5010-0803	TI5910-0802	TI5910-0803	3-edge tipped
TI5010-0805	TI5010-3608	TI5010-0806	TI5010-0807	TI5010-0808	TI5910-0807	TI5910-0808	3-edge tipped

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	
TI5010-0815		TI5010-0816	TI5010-0817	TI5010-0818	TI5910-0817	TI5910-0818	6-edge tipped
TI5010-0820		TI5010-0821	TI5010-0822	TI5010-0823	TI5910-0822	TI5910-0823	6-edge tipped
TI5010-0825		TI5010-0826	TI5010-0827	TI5010-0828	TI5910-0827	TI5910-0828	6-edge tipped
TI5010-0830		TI5010-0831	TI5010-0832	TI5010-0833	TI5910-0832	TI5910-0833	6-edge tipped

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com


All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete **holder program** in our tool holder catalog or in our online shop.

Subject to technical changes.

VBGW

edge tipped



				P25BH	P45BH	K65BH	K85BH	S85BH
ISO Code	IC	S	R	Item No.				
VBGW-1.21.50-2	.156	.094	.004			TI5510-1264		
VBGW-1.21.50.5-2	.156	.094	.008	TI5510-0840	TI5510-0841	TI5510-0842	TI5510-0843	TI5510-3652
VBGW-1.21.51-2	.156	.094	.016	TI5510-0845	TI5510-0846	TI5510-0847	TI5510-0848	TI5510-3654
VBGW-21.50-2	.250	.094	.004			TI5510-1265		
VBGW-21.50.5-2	.250	.094	.008	TI5510-0855	TI5510-0856	TI5510-0857	TI5510-0858	TI5510-3672
VBGW-21.51-2	.250	.094	.016	TI5510-0860	TI5510-0861	TI5510-0862	TI5510-0863	TI5510-3674
VBGW21.52-2	.250	.094	.031	TI5510-0865	TI5510-0866	TI5510-0867	TI5510-0868	TI5510-3676
VBGW-330-2	.375	.187	.004			TI5510-1267		
VBGW-330.5-2	.375	.187	.008	TI5510-0875	TI5510-0876	TI5510-0877	TI5510-0878	TI5510-3682
VBGW-331-2	.375	.187	.016	TI5510-0880	TI5510-0881	TI5510-0882	TI5510-0883	TI5510-3684
VBGW-332-2	.375	.187	.031	TI5510-0885	TI5510-0886	TI5510-0887	TI5510-0888	TI5510-3686

Standard

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL ^{low}	H45BL	H65BL	H85BL	X90BH	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Version
TI5010-1264					TI5910-1264		2-edge tipped
TI5010-0840	TI5010-3652	TI5010-0841	TI5010-0842	TI5010-0843	TI5910-0842	TI5910-0843	2-edge tipped
TI5010-0845	TI5010-3654	TI5010-0846	TI5010-0847	TI5010-0848	TI5910-0847	TI5910-0848	2-edge tipped
TI5010-1265					TI5910-1265		2-edge tipped
TI5010-0855	TI5010-3672	TI5010-0856	TI5010-0857	TI5010-0858	TI5910-0857	TI5910-0858	2-edge tipped
TI5010-0860	TI5010-3674	TI5010-0861	TI5010-0862	TI5010-0863	TI5910-0862	TI5910-0863	2-edge tipped
TI5010-0865	TI5010-3676	TI5010-0866	TI5010-0867	TI5010-0868	TI5910-0867	TI5910-0868	2-edge tipped
TI5010-1267					TI5910-1267		2-edge tipped
TI5010-0875	TI5010-3682	TI5010-0876	TI5010-0877	TI5010-0878	TI5910-0877	TI5910-0878	2-edge tipped
TI5010-0880	TI5010-3684	TI5010-0881	TI5010-0882	TI5010-0883	TI5910-0882	TI5910-0883	2-edge tipped
TI5010-0885	TI5010-3686	TI5010-0886	TI5010-0887	TI5010-0888	TI5910-0887	TI5910-0888	2-edge tipped

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com


All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.

Subject to technical changes.

VCGW

edge tipped



	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.				
MiniTools	VCGW 050101 (CL 2,00)	.122	.062	.004			TI5510-2528		
	VCGW 050102 (CL 2,00)	.122	.062	.008			TI5510-2530		
	VCGW 050104 (CL 2,00)	.122	.062	.016			TI5510-2532		
Standard	VCGW -1.21.50-2	.156	.094	.004			TI5510-1274		
	VCGW -1.21.50.5-2	.156	.094	.008	TI5510-0960	TI5510-0961	TI5510-0962	TI5510-0963	TI5510-3702
	VCGW -1.21.51-2	.156	.094	.016	TI5510-0965	TI5510-0966	TI5510-0967	TI5510-0968	TI5510-3704
	VCGW -220-2	.250	.125	.004			TI5510-1275		
	VCGW -220.5-2	.250	.125	.008	TI5510-0975	TI5510-0976	TI5510-0977	TI5510-0978	TI5510-3722
	VCGW -221-2	.250	.125	.016	TI5510-0980	TI5510-0981	TI5510-0982	TI5510-0983	TI5510-3724
	VCGW -222-2	.250	.125	.031	TI5510-0985	TI5510-0986	TI5510-0987	TI5510-0988	TI5510-3726
	VCGW -330-2	.375	.187	.004			TI5510-1277		
	VCGW -330.5-2	.375	.187	.008	TI5510-0995	TI5510-0996	TI5510-0997	TI5510-0998	TI5510-3742
	VCGW -331-2	.375	.187	.016	TI5510-1000	TI5510-1001	TI5510-1002	TI5510-1003	TI5510-3744
Sharp	VCGW -332-2	.375	.187	.031	TI5510-1005	TI5510-1006	TI5510-1007	TI5510-1008	TI5510-3746
	VCGW -333-2	.375	.187	.047	TI5510-1010	TI5510-1011	TI5510-1012	TI5510-1013	TI5510-3748
	VCGW 1.21.50.5F-2	.156	.094	.008	TI5510-2372	TI5510-2472	TI5510-2672	TI5510-2772	TI5510-2872
	VCGW -1.21.51F-2	.156	.094	.016	TI5510-2374	TI5510-2474	TI5510-2674	TI5510-2774	TI5510-2874
	VCGW -220.5F-2	.250	.125	.008	TI5510-2382	TI5510-2482	TI5510-2682	TI5510-2782	TI5510-2882
	VCGW -221F-2	.250	.125	.016	TI5510-2384	TI5510-2484	TI5510-2684	TI5510-2784	TI5510-2884
VCGW -330.5F-2	.375	.187	.008	TI5510-2392	TI5510-2492	TI5510-2692	TI5510-2792	TI5510-2892	
VCGW -331F-2	.375	.187	.016	TI5510-2394	TI5510-2494	TI5510-2694	TI5510-2794	TI5510-2894	

i Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL ^{low}	H45BL	H65BL	H85BL	X90BH	X95BH	Version
			TI5010-1561		TI5910-2528		2-edge tipped
			TI5010-1562		TI5910-2530		2-edge tipped
			TI5010-1563		TI5910-2532		2-edge tipped
TI5010-1274					TI9510-1274		2-edge tipped
TI5010-0960	TI5010-3702	TI5010-0961	TI5010-0962	TI5010-0963	TI5910-0962	TI5910-0963	2-edge tipped
TI5010-0965	TI5010-3704	TI5010-0966	TI5010-0967	TI5010-0968	TI5910-0967	TI5910-0968	2-edge tipped
TI5010-1275					TI5910-1275		2-edge tipped
TI5010-0975	TI5010-3722	TI5010-0976	TI5010-0977	TI5010-0978	TI5910-0977	TI5910-0978	2-edge tipped
TI5010-0980	TI5010-3724	TI5010-0981	TI5010-0982	TI5010-0983	TI5910-0982	TI5910-0983	2-edge tipped
TI5010-0985	TI5010-3726	TI5010-0986	TI5010-0987	TI5010-0988	TI5910-0987	TI5910-0988	2-edge tipped
TI5010-1277					TI5910-1277		2-edge tipped
TI5010-0995	TI5010-3742	TI5010-0996	TI5010-0997	TI5010-0998	TI5910-0997	TI5910-0998	2-edge tipped
TI5010-1000	TI5010-3744	TI5010-1001	TI5010-1002	TI5010-1003	TI5910-1002	TI5910-1003	2-edge tipped
TI5010-1005	TI5010-3746	TI5010-1006	TI5010-1007	TI5010-1008	TI5910-1007	TI5910-1008	2-edge tipped
TI5010-1010	TI5010-3748	TI5010-1011	TI5010-1012	TI5010-1013	TI5910-1012	TI5910-1013	2-edge tipped
TI5010-2472	TI5010-2572	TI5010-2672	TI5010-2772		TI5910-2672		2-edge tipped
TI5010-2474	TI5010-2574	TI5010-2674	TI5010-2774		TI5910-2674		2-edge tipped
TI5010-2482	TI5010-2582	TI5010-2682	TI5010-2782		TI5910-2682		2-edge tipped
TI5010-2484	TI5010-2584	TI5010-2684	TI5010-2784		TI5910-2684		2-edge tipped
TI5010-2492	TI5010-2592	TI5010-2692	TI5010-2792		TI5910-2692		2-edge tipped
TI5010-2494	TI5010-2594	TI5010-2694	TI5010-2794		TI5910-2694		2-edge tipped

i You will find the matching boring bar holder in our boring bar catalog [03] on page 28.

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com


All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.


Subject to technical changes.

VNGA

edge tipped



	P25BH	P45BH	K65BH	K85BH	S85BH			
ISO Code	IC	S	R	Item No.				
VNGA-330.5-2	.375	.187	.008	TI5510-1020	TI5510-1021	TI5510-1022	TI5510-1023	TI5510-3782
VNGA-331-2	.375	.187	.016	TI5510-1025	TI5510-1026	TI5510-1027	TI5510-1028	TI5510-3784
VNGA-332-2	.375	.187	.031	TI5510-1030	TI5510-1031	TI5510-1032	TI5510-1033	TI5510-3786
VNGA-333-2	.375	.187	.047	TI5510-1035	TI5510-1036	TI5510-1037	TI5510-1038	TI5510-3788



	P25BH	P45BH	K65BH	K85BH	S85BH			
ISO Code	IC	S	R	Item No.	Item No.	Item No.	Item No.	Item No.
VNGA-330.5-4	.375	.187	.008	TI5510-1045	TI5510-1046	TI5510-1047	TI5510-1048	
VNGA-331-4	.375	.187	.016	TI5510-1050	TI5510-1051	TI5510-1052	TI5510-1053	
VNGA-332-4	.375	.187	.031	TI5510-1055	TI5510-1056	TI5510-1057	TI5510-1058	
VNGA-333-4	.375	.187	.047	TI5510-1060	TI5510-1061	TI5510-1062	TI5510-1063	

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

	H25BL	H35BL ^{low}	H45BL	H65BL	H85BL	X90BH	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Version
TI5010-1020	TI5010-3782	TI5010-1021	TI5010-1022	TI5010-1023	TI5910-1022	TI5910-1023		2-edge tipped
TI5010-1025	TI5010-3784	TI5010-1026	TI5010-1027	TI5010-1028	TI5910-1027	TI5910-1028		2-edge tipped
TI5010-1030	TI5010-3786	TI5010-1031	TI5010-1032	TI5010-1033	TI5910-1032	TI5910-1033		2-edge tipped
TI5010-1035	TI5010-3788	TI5010-1036	TI5010-1037	TI5010-1038	TI5910-1037	TI5910-1038		2-edge tipped

	H25BL	H35BL	H45BL	H65BL	H85BL	X90BH	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Version
TI5010-1045		TI5010-1046	TI5010-1047	TI5010-1048	TI5910-1047	TI5910-1048		4-edge tipped
TI5010-1050		TI5010-1051	TI5010-1052	TI5010-1053	TI5910-1052	TI5910-1053		4-edge tipped
TI5010-1055		TI5010-1056	TI5010-1057	TI5010-1058	TI5910-1057	TI5910-1058		4-edge tipped
TI5010-1060		TI5010-1061	TI5010-1062	TI5010-1063	TI5010-1062	TI5010-1063		4-edge tipped

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com


All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.

Subject to technical changes.

VXGW

edge tipped



	P25BH	P45BH	K65BH	K85BH	S85BH
ISO Code	IC	S	R	Item No.	Item No.
VXGW-330	.375	.187	.004		TI5510-1650
VXGW-330.5	.375	.187	.008		TI5510-1655
VXGW-331	.375	.187	.016		TI5510-1660


DTS-Specials

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Version
TI5010-1650					TI5910-1650		1-edge tipped
TI5010-1655					TI5910-1655		1-edge tipped
TI5010-1660					TI5910-1660		1-edge tipped

Specials Face / Axial Machining



Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com



All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.

Subject to technical changes.

WCGW

edge tipped



MiniTools

ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
WCGW-1.210-3	.156	.062	.004					
WCGW-1.210.5-3	.156	.062	.008					
WCGW-1.211-3	.156	.062	.016					

You will find the matching boring bar holder in our boring bar catalog [03] on page 33.

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

H25BL	H35BL	H45BL	H65BL	H85BL	X90BH	X95BH	Version
			TI5010-1571		TI5910-2534		3-edge tipped
			TI5010-1572		TI5910-2536		3-edge tipped
			TI5010-1573		TI5910-2538		3-edge tipped

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Special tools on request for you!
Please send inquiries to sales@ranitool.com


All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete **holder program** in our tool holder catalog or in our online shop.


Subject to technical changes.

WNGA

edge tipped



	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.				
Standard	WNGA-430.5-3	.500	.187	.008	TI5510-1070	TI5510-1071	TI5510-1072	TI5510-1073	TI5510-3902
	WNGA-431-3	.500	.187	.016	TI5510-1075	TI5510-1076	TI5510-1077	TI5510-1078	TI5510-3904
	WNGA-432-3	.500	.187	.031	TI5510-1080	TI5510-1081	TI5510-1082	TI5510-1083	TI5510-3906
	WNGA-433-3	.500	.187	.047	TI5510-1085	TI5510-1086	TI5510-1087	TI5510-1088	
Wiper	WNGA-431W-3	.500	.187	.016	TI5510-1095	TI5510-1096	TI5510-1097	TI5510-1098	
	WNGA-432W-3	.500	.187	.031	TI5510-1100	TI5510-1101	TI5510-1102	TI5510-1103	
	WNGA-433W-3	.500	.187	.047	TI5510-1105	TI5510-1106	TI5510-1107	TI5510-1108	



	ISO Code	IC	S	R	P25BH	P45BH	K65BH	K85BH	S85BH
					Item No.	Item No.	Item No.	Item No.	Item No.
Standard	WNGA-430.5-6	.500	.187	.008	TI5510-1115	TI5510-1116	TI5510-1117	TI5510-1118	
	WNGA-431-6	.500	.187	.016	TI5510-1120	TI5510-1121	TI5510-1122	TI5510-1123	
	WNGA-432-6	.500	.187	.031	TI5510-1125	TI5510-1126	TI5510-1127	TI5510-1128	
	WNGA-433-6	.500	.187	.047	TI5510-1130	TI5510-1131	TI5510-1132	TI5510-1133	
Wiper	WNGA-431W-6	.500	.187	.016	TI5510-1140	TI5510-1141	TI5510-1142	TI5510-1143	
	WNGA-432W-6	.500	.187	.031	TI5510-1145	TI5510-1146	TI5510-1147	TI5510-1148	
	WNGA-433W-6	.500	.187	.047	TI5510-1150	TI5510-1151	TI5510-1152	TI5510-1153	

Application range:

- CBN-P Sintered Steel ...
- CBN-K Grey Cast Iron (GCI), Ductile Cast Iron (DCI) ...
- CBN-S Ni-, Co-, Fe- and Cr-Alloys, Titanium, Titanium Alloys ...
- CBN-H Steel hardened up to 72 HRC, Cast Iron hardened ...
- CBN-X Tool Steel hardened, Stellite, Stainless Steel hardened, powder metallurgical Steel ...

You will find further application ranges in the detailed overview on page 7.

Detailed informations about cutting parameters and cooling can be found on page 56.

- continuous cut
- light interrupted cut
- heavy interrupted cut

	H25BL	H35BL	H45BL	H65BL	H85BL	X90BH	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Version
TI5010-1070			TI5010-1071	TI5010-1072	TI5010-1073	TI5910-1072	TI5910-1073	3-edge tipped
TI5010-1075			TI5010-1076	TI5010-1077	TI5010-1078	TI5910-1077	TI5910-1078	3-edge tipped
TI5010-1080			TI5010-1081	TI5010-1082	TI5010-1083	TI5910-1082	TI5910-1083	3-edge tipped
TI5010-1085			TI5010-1086	TI5010-1087	TI5010-1088	TI5910-1087	TI5910-1088	3-edge tipped
TI5010-1095			TI5010-1096	TI5010-1097	TI5010-1098	TI5910-1097	TI5910-1098	3-edge tipped
TI5010-1100			TI5010-1101	TI5010-1102	TI5010-1103	TI5910-1102	TI5910-1103	3-edge tipped
TI5010-1105			TI5010-1106	TI5010-1107	TI5010-1108	TI5910-1107	TI5910-1108	3-edge tipped

	H25BL	H35BL	H45BL	H65BL	H85BL	X90BH	X95BH	Version
Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Version
TI5010-1115			TI5010-1116	TI5010-1117	TI5010-1118	TI5910-1117	TI5910-1118	6-edge tipped
TI5010-1120			TI5010-1121	TI5010-1122	TI5010-1123	TI5910-1122	TI5910-1123	6-edge tipped
TI5010-1125			TI5010-1126	TI5010-1127	TI5010-1128	TI5910-1127	TI5910-1128	6-edge tipped
TI5010-1130			TI5010-1131	TI5010-1132	TI5010-1133	TI5910-1132	TI5910-1133	6-edge tipped
TI5010-1140			TI5010-1141	TI5010-1142	TI5010-1143	TI5910-1142	TI5910-1143	6-edge tipped
TI5010-1145			TI5010-1146	TI5010-1147	TI5010-1148	TI5910-1147	TI5910-1148	6-edge tipped
TI5010-1150			TI5010-1151	TI5010-1152	TI5010-1153	TI5910-1152	TI5910-1153	6-edge tipped

Special tools on request for you!
Please send inquiries to sales@ranitool.com

All our products are also available in the online shop.
Visit us at ranitool.com

You can find our complete holder program in our tool holder catalog or in our online shop.

Subject to technical changes.

Cutting Parameters

for our CBN Grades

Vc X 3.28 = SFM

Ap / 25.4 = DOC inches

F / 25.4 = inch per revolution

-  continuous cut
-  light interrupted cut
-  heavy interrupted cut

Material		P25BH			P45BH			K65BH			K85BH			S85BH		
		V _c [m/min]	a _p [mm]	F [mm/rev]												
Grey Cast Iron (GCI)	min.							500	0,01	0,01	450	0,01	0,01			
	max.							2000	2,80	0,40	1400	2,80	0,35			
Ductile Cast Iron (DCI)	min.							250	0,01	0,01	200	0,01	0,01			
	max.							1200	2,80	0,35	1000	2,80	0,30			
Sintered Steel	min.	200	0,01	0,01	180	0,01	0,01									
	max.	400	2,60	0,30	300	2,00	0,30									
Ni-, Co-, Fe- and Cr-Alloys	min.												80	0,01	0,01	
	max.												350	0,50	0,30	
Titanium	min.												80	0,01	0,01	
	max.												240	0,50	0,30	

Subject to technical changes.


 Cutting parameters for hard turning can be found on page 58.

Cooling recommended

In machining with CBN inserts, proper cooling is a key to successful machining.

Here you will find our recommendation:

		Dry	Air	Emulsion	Oil
P		4. Choice	3. Choice	1. Choice	2. Choice
		2. Choice	1. Choice		
		2. Choice	1. Choice		
K		4. Choice	3. Choice	1. Choice	2. Choice
		2. Choice	1. Choice		
		2. Choice	1. Choice		
S			3. Choice	1. Choice	2. Choice
			2. Choice	1. Choice	
			2. Choice	1. Choice	



Never use max. ap with max. feed rate

Significantly higher cutting depths and feeds can be realized with RNGN and SNGN Solid inserts.



If you have any further technical questions, please do not hesitate to contact us by phone or e-mail!

Phone: 888.554.7264

Mail: sales@ranitool.com

Cutting Parameters

for our CBN Grades

Vc X 3.28 = SFM

Ap / 25.4 = DOC inches

F / 25.4 = inch per revolution

Vc X 3.28 = SFM

Ap / 25.4 = DOC inches

F / 25.4 = inch per revolution

-  continuous cut
-  light interrupted cut
-  heavy interrupted cut

Material		H25BL			H35BL			H45BL			H65BL			H85BL		
		V _c [m/min]	a _p [mm]	F [mm/rev]												
Steel hardened up to 72 HRC	min.	100	0,01	0,01	100	0,01	0,01	100	0,01	0,01	100	0,01	0,01	80	0,01	0,01
	max.	300	1,50	0,50	260	1,50	0,50	260	1,00	0,40	240	1,00	0,40	220	1,00	0,40
Ball Bearing and Spring Steel	min.	100	0,01	0,01	100	0,01	0,01	100	0,01	0,01	100	0,01	0,01	80	0,01	0,01
	max.	400	1,00	0,30	360	1,00	0,50	360	0,50	0,50	360	0,50	0,50	200	0,40	0,30
Tool Steel, hardened up to 72 HRC	min.															
	max.															
Case hardened Steel	min.	100	0,01	0,01	100	0,01	0,01	100	0,01	0,01	100	0,01	0,01	80	0,01	0,01
	max.	300	1,50	0,50	260	1,50	0,50	260	1,00	0,40	240	1,00	0,40	220	1,00	0,40
Powder metallurgical Steel, hardened up to 72 HRC	min.															
	max.															
Cast Iron, hardened	min.	80	0,01	0,01	80	0,01	0,01	80	0,01	0,01	80	0,01	0,01	60	0,01	0,01
	max.	220	1,50	0,50	200	1,00	0,50	200	1,00	0,50	200	1,00	0,50	180	0,50	0,30
Sintered Steel, hardened	min.	100	0,01	0,01	100	0,01	0,01	100	0,01	0,01	100	0,01	0,01	80	0,01	0,01
	max.	300	1,50	0,50	260	1,50	0,50	260	1,00	0,40	240	1,00	0,40	220	1,00	0,40
Stainless Steel, hardened	min.															
	max.															
Stellite	min.															
	max.															
Hard and Soft Machining	min.	80	0,01	0,01	80	0,01	0,01	80	0,01	0,01	80	0,01	0,01	80	0,01	0,01
	max.	400	1,50	0,40	360	1,50	0,30	300	1,50	0,30	300	1,50	0,30	260	1,00	0,30


X90BH			X95BH		
V _c [m/min]	a _p [mm]	F [mm/rev]	V _c [m/min]	a _p [mm]	F [mm/rev]
100	0,01	0,01	60	0,01	0,01
260	1,00	0,40	180	0,50	0,30
60	0,01	0,01	60	0,01	0,01
220	0,50	0,40	180	0,30	0,30
80	0,01	0,01	60	0,01	0,01
200	2,00	0,40	160	0,50	0,30
60	0,01	0,01	40	0,01	0,01
160	0,50	0,30	120	0,30	0,30

Cooling recommended

In machining with CBN inserts, proper cooling is a key to successful machining.

Here you will find our recommendation:

		Dry	Air	Emulsion	Oil
H		4. Choice	3. Choice	1. Choice	2. Choice
		2. Choice	1. Choice	3. Choice	
		2. Choice	1. Choice		
X		4. Choice	3. Choice	1. Choice	2. Choice
		2. Choice	1. Choice		
		2. Choice	1. Choice		



Never use max. ap with max. feed rate


Significantly higher cutting depths and feeds can be realized with RNGN and SNGN Solid inserts.



If you have any further technical questions, please do not hesitate to contact us by phone or e-mail!

Phone: 888.554.7264

Mail: sales@ranitool.com



Copyright:


The reprint of our catalogs, copies of our flyers and newsletters or only excerpts such as illustrations, designs, technical information and design require the written permission of Rani Tool Corp. Copies or only excerpts such as illustrations, designs, technical information from our homepage and our online store are only permitted with the written consent of Rani Tool Corp.

All rights are reserved. Errors, misprints or printing errors do not entitle to claims. The pictorial and graphic representation of our tools do not necessarily have to correspond to the actual tool in all details.

We reserve the right to make production-related technical changes and changes to the delivery program. The cutting values given are guide values which must be adjusted according to the process environment.

Safety Instructions:

- ▶ Tools equipped with ultra-hard cutting edges are very sharp laser cut tools.
- ▶ Careful handling of the tools during unpacking and their use is recommended.
- ▶ Wearing protective gloves reduces the risk of injury.
- ▶ Material chipping and tool breakage may occur during machining, wearing safety glasses is recommended.
- ▶ Balanced holders are recommended for speeds above 10,000 rpm.
- ▶ We do not accept any responsibility for tools that have been modified, reground or used incorrectly and beyond their normal service life.
- ▶ Protective goggles are recommended when using DTS tools, sparks may also occur, make sure that no fire can occur.



DTS GmbH

Diamond Tooling Systems

PASSION FOR DIAMOND



Rani Tool Corp.

320 Troy Circle, Unit C, Knoxville, TN 37919

**Tel: (865) 337-7799 or (888) 554-RANI • Fax: (865) 337-7716
E-mail: sales@ranitool.com • www.ranitool.com**